

PRODUCT DATA SHEET

MA C 50/150





ADVANTAGES

- Handle - Equipped with a pressure regulator - CE approved 50L tank equipped with all safety devices: air pressure gauge, safety valve, nonreturn valve and air outlet valve

This compressor is studied for all types of use.

It is equipped with a cylinder head with a cast iron cylinder for better cooling and longevity.







FEATURES

POWER SUPPLY	230 V 1ph / 50 Hz
NOMINAL CURRENT INTENSITY	approx. 9.8 A
MOTOR POWER	2.5 CV - 1.8 kW
CYLINDER NB / STAGE NB	1 (in cast iron) / 1
AIR PUMP ROTATION SPEED	2850 rpm
AIR DISPLACEMENT	8.2 cfm - 150 L/min

MAX. PRESSURE	8 BAR - 116 PSI
AIR OUTLET	regulated LV quick coupling (ISO6150 B)
SOUND LEVEL	62 dB(A) at 1 meter
NET DIMENSIONS **	L. 700 x W. 300 x H. 690 mm
GROSS DIMENSIONS **	L. 730 x W. 415 x H. 700 mm
NET / GROSS WEIGHT **	29 / 32.5 kg

- * Warranty according to our General Terms of Sales while following the maintenance schedule and respecting the operation and installation recommendation. ** Weights and dimensions are given as information only and are subject to change without prior notice.

PACKAGING

MAX. PRODUCTS NB BY "EUROPE" PALLET	6
GROSS DIMENSIONS (PRODUCTS + "EUROPE" PALLET) **	L. 1200 x W. 800 x H. 1550 mm
GROSS WEIGHT (PRODUCTS + "EUROPE" PALLET) **	220 kg

